



industrial

GOODRAM Commercial microSD Memory Card 3D TLC DATASHEET

Version: 1.0
Date: July 2020

SD Card for Industrial Applications

Wilk Elektronik S.A.
Mikołowska 42
43-173 Łaziska Górne, Poland
Tel.: +48 32 736 90 00, Fax.: +48 32 736 90 01
E-mail: sales@goodram.com

All rights are strictly reserved. Any portion of this paper shall not be reproduced, copied or translated to any other forms without permission from Wilk Elektronik S.A.

This document is subject to change without any notice.

Please contact your Wilk Elektronik S.A. sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. Wilk Elektronik S.A. assumes no liability for damages or losses occurring as a result of noncompliance with applicable laws and regulations.



industrial

GOODRAM 3D TLC commercial microSD

REVISION HISTORY

VERSION	CHANGES	DATE
1.0	Initial release	21.07.2020



industrial

TABLE OF CONTENTS

REVISION HISTORY 3

PRODUCT OVERVIEW 5

PRODUCT DETAILS..... 6

GENERAL DESCRIPTION..... 6

PIN ASSIGNMENT 6

FLASH MANAGEMENT 7

STANDARDS & REFERENCES 10

SAFETY PRECAUTIONS 10

NOTES ON USAGE 11

PRODUCT OVERVIEW

- | | |
|--|---|
| <ul style="list-style-type: none"> • Capacity: <ul style="list-style-type: none"> ◦ 16GB – 128GB • Bus Speed Mode <ul style="list-style-type: none"> ◦ UHS-I • Speed Class <ul style="list-style-type: none"> ◦ Class 10 • Flash <ul style="list-style-type: none"> ◦ Kioxia 3D TLC • Power Consumption^{Note1} <ul style="list-style-type: none"> ◦ Power Up Current < 250uA ◦ Standby Current < 1000uA ◦ Read Current < 400mA ◦ Write Current < 400mA • CPRM (Content Protection for Recordable Media) • EMI compliant • RoHS compliant | <ul style="list-style-type: none"> • Support CPRM • Support SD SPI mode • Controller <ul style="list-style-type: none"> ◦ PS8131 • Endurance <ul style="list-style-type: none"> ◦ Data retention over 10 years in room temperature (25°C)^{Note2} • Advanced Flash Management <ul style="list-style-type: none"> ◦ Static and Dynamic Wear Levelling ◦ Bad Block Management • Write Protect with mechanical switch • Operating Voltage range <ul style="list-style-type: none"> ◦ 2.7 – 3.6 V • Temperature Range^{Note3} <ul style="list-style-type: none"> ◦ Operation 0°C ~ +85°C ◦ Storage: -40°C ~ +85°C |
|--|---|

Notes:

1. Please see "Power Consumption" for details.
2. In new product
3. According to IEC-60068-2-1/2/14/38 standard.


PRODUCT DETAILS

GENERAL DESCRIPTION

The Micro Secure Digital (microSD) card is fully compliant to the specification released by SD Card Association. The Command List supports [Part 1 Physical Layer Specification Ver6.10 Final] definitions. Card Capacity of non-secure area and secure area support [Part 3 Security Specification Ver7.0 Final] Specifications.

The microSD card is based on 8-pin interface, designed to operate at a maximum operating frequency of 208MHz. It can alternate communication protocol between the SD mode and SPI mode. It performs data error detection and correction with very low power consumption.

PIN ASSIGNMENT



PIN	SD MODE			SPI MODE		
	NAME	TYPE	DESCRIPTION	NAME	TYPE	DESCRIPTION
1	DAT2	I/O/PP	Data Line [bit2]	RSV		
2	CD/DAT3	I/O/PP	Card Detect/ Data Line [bit3]	CS	I	Chip Select (neg true)
3	CMD	PP	Command/Response	DI	I	Data In
4	VDD	S	Supply Voltage	VDD	S	Supply voltage
5	CLK	I	Clock	SCLK	I	Clock
6	VSS	S	Supply voltage ground	VSS	S	Supply voltage ground
7	DAT0	I/O/PP	Data Line [bit0]	DO	O/PP	Data Out
8	DAT1	I/O/PP	Data Line [bit1]	RSV		

FLASH MANAGEMENT

GOODRAM microSD card utilizes all the state of art technologies to ensure full reliability until the specified NAND Flash program/erase cycles parameter is reached. These technologies include but are not limited to:

Error Correction Code (ECC)

Flash memory cells will deteriorate with use, which may generate random bit errors in the stored data. To ensure the highest reliability, GOODRAM microSD card applies the ECC Algorithm, which can detect and correct errors that occur during read process, to ensure data is read correctly, as well as protected from corruption.

Wear Levelling

Storage devices based on NAND flash memory, can only undergo a limited number of program/erase cycles, and due to various usage scenarios, data may not be distributed evenly between NAND flash chips. If a certain area gets updated more frequently than others, the lifetime of the device will be reduced significantly. Wear Leveling algorithm used in GOODRAM microSD cards is used to extend the lifespan of NAND Flash by evenly distributing write and erase cycles across the whole storage area. Moreover, by utilizing both dynamic and static Wear Leveling algorithms, the life expectancy of GOODRAM microSD cards can meet the listed specification.

Bad Block Management

Bad blocks are blocks that include one or more invalid bits, and their reliability is not guaranteed. Blocks that are identified and marked as bad by the manufacturer are referred to as "Initial Bad Blocks". Bad blocks that are developed during the lifespan of the flash are named "Later Bad Blocks". GOODRAM microSD card uses an efficient bad block management algorithm to detect all types of bad blocks, which further prevents data being stored into them and improves the data reliability.

industrial

COMPARING SD3.0, SDHC AND SDXC

	SD3.0 Standard (Backward compatible to 2.0 host)	SD3.0 SDHC/SDXC (Backward compatible to 2.0 host)
Addressing Mode	Byte (1 byte unit)	Block (512 byte unit)
HCS/CCS bits of ACMD41	Support	Support
CMD8 (SEND_IF_COND)	Support	Support
CMD16 (SET_BLOCKLEN)	Support	Support (Only CMD42)
Partial Read	Support	Not Support
Lock/Unlock Function	Mandatory	Mandatory
Write Protect Groups	Optional	Not Support
Supply Voltage 2.0v – 2.7v (for initialization)	Support	Support
Total Bus Capacitance for each signal line	40pF	40pF
CSD Version (CSD_STRUCTURE Value)	1.0 (0x0)	2.0 (0x1)
Speed Class	Optional	Mandatory (Class 2/4/6/10)

ELECTRICAL SPECIFICATIONS

Bus Speed Mode	Max. Power Up Current (μ A)	Max. Standby Current (μ A)	Max. Read Current (mA)	Max. Write Current (mA)
Default Speed Mode	250	1000	150 @ 3.6V	150 @ 3.6V
High Speed Mode	250	1000	200 @ 3.6V	200 @ 3.6V
UHS-I Mode	UHS50/DDR50	250	1000	400 @ 3.6V
	UHS104	250	1000	400 @ 3.6V

Note:

- 1 Data transfer mode is single channel.
- 2 Power Consumption may differ according to flash configuration, SDR configuration, or platform.

PARAMETER	RATING
Operating voltage	2.7 – 3.6V +/- 5%

Temperature specification

SYMBOL	PARAMETER	MIN.	MAX.	UNIT
T _a	Operating Temperature	0	+85	°C
T _{st}	Storage Temperature	-40	+85	°C

industrial

PERFORMANCE


Capacity	Density	Flash type	Performance	
			TestMetrix test	
			Read (MB/s)	Write (MB/s)
16GB	128Gb x 1	BiCs 3	100.7	36.83
32GB	128Gb x 2	BiCs 3	100.91	73.22
	256Gb x 1	BiCs 3	100.91	37.57
64GB	128Gb x 4	BiCs 3	100.90	85.09
	256Gb x 2	BiCs 3	100.90	72.11
128GB	256Gb x 4	BiCs 3	100.90	85.09
256GB	256Gb x 8	BiCs 3	100.83	84.13

PRODUCT ORDERING INFORMATION

PN	Type	Capacity	Technology	Temp range	Grade
RUSDUT016U1SB-P8DKID	microSD	16 GB	3D TLC	0°C ~70°C	commercial
RUSDUT032U1SB-P8DKID	microSD	32 GB	3D TLC	0°C ~70°C	commercial
RUSDUT064U1SB-P8DKID	microSD	64 GB	3D TLC	0°C ~70°C	commercial
RUSDUT128U1SB-P8DKID	microSD	128 GB	3D TLC	0°C ~70°C	commercial
RUSDUT256U1SB-P8DKID	microSD	256 GB	3D TLC	0°C ~70°C	commercial

PHYSICAL DIMENSION

Dimensions: 15mm (L) * 11mm (W) * 1mm (H)



STANDARDS & REFERENCES

The following table is to list out the standards that have been adopted for designing the product.

STANDARD USED	ACRONYM/SOURCE
RoHS	Restriction of Hazardous Substances Directive
SD specification	http://www.sdcard.org
CE	Consumer electronics certification; please contact us for further information.

SAFETY PRECAUTIONS

Do not bend, crush, drop, or place heavy objects on top of the Product. Do not use tweezers, pliers or similar items that could damage the Product. Take particular care when inserting or removing the Product. Stop using the Product when the Product does not work properly. Failure to follow these instructions could result in fire, damage to the Product and/or other property, and/or personal injury including burns and electric shock.

Keep out of reach of small children. Accidental swallowing may cause suffocation or injury. Contact a doctor immediately if you suspect a child has swallowed the Product.

Do not directly touch the interface pins, put them in contact with metal, strike them with hard objects or cause them to short. Do not expose to static electricity.

Do not disassemble or modify the Product. This may cause electric shock, damage to the Product or fire.

NOTES ON USAGE

The Product contains nonvolatile semiconductor memory. Do not use the Product in accordance with a method of usage other than that written in the manual. This may cause the destruction or loss of data.

To protect against accidental data loss, you should back up your data frequently on more than one type of storage media. Wilk Elektronik S.A. assumes no liability for destruction or loss of data recorded on the Card for any reason.

When used over a long period of time or repeatedly, the reading, writing and deleting capabilities of the Product will eventually fail, and the performance speed of the Product may decrease below the original speed specific to the Product's applicable class.

If the Product is to be transferred or destroyed, note that the data it contained may still be recoverable unless it is permanently deleted by third-party deletion software or similar means beforehand.

Product is intended for use in general electronics applications and selected industrial applications and any other specific applications as expressly stated in this document. Product is neither intended nor warranted for use in equipment or systems where failure may cause loss of human life, bodily injury, serious property damage or serious public impact ("Unintended Use"). Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, medical equipment or equipment used to control combustions or explosions. Do not use Product for Unintended Use unless specifically permitted in this document.

No parts of this document may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electric, photocopying, recording or otherwise, without permission of Wilk Elektronik S.A.

Wilk Elektronik S.A does not make any warranty, express or implied, with respect to this document, including as to licensing, Non-infringement, merchantability or fitness for a particular purpose.