

PX400

SSD

Main features

- PCIe gen 3 x2 interface
- 30x faster than hard drive
- Heat-dissipating thermal pad
- 3-year warranty with free technical support



Performance

Parameter	256 GB	512 GB
Sequential read performance (max.) ¹	1 550 MB/s	1 590 MB/s
Sequential write performance (max.) ¹	850 MB/s	1 000 MB/s
Random read performance (4k QD64)(max.) ²	170 000 IOPS	200 000 IOPS
Random write performance (4K QD64)(max.) ²	150 000 IOPS	160 000 IOPS

Physical parameters

Capacities ³	256GB, 512GB
Dimensions	22 x 80 mm
Interface	M.2 PCIe NVMe gen 3 x2 (B+M)
NAND Flash	3D NAND
Controller	Phison PS5008-E8

Reliability and environmental

Technologies	SmartECC™, SmartFlush™, Guaranteed Flush™, SmartZIP™
MTBF	1 500 000 hours
Temperature	Operating: 0 ~ 70°C; Storage: -45 ~ 85°C
Warranty	3 years with free technical support

Ordering information

Product	Capacity	Packaging	P/N	EAN
SSD PX400	256 GB	Includes SSD	SSDPR-PX400-256-80	5908267922958
	512 GB		SSDPR-PX400-512-80	5908267922965

¹ Based on tests performed in Crystal Disk Mark 3.0.3 on SSD in FOB (fresh-out-of-box) state. Actual results may vary depending on your system configuration or SSD wear.

² Based on tests performed in Iometer on SSD in FOB (fresh-out-of-box) state. Actual results may vary depending on your system configuration or SSD wear.

³ Storage capacity for GOODRAM SSD is provided in decimal values, i.e. 1GB = 1 000 000 000 bytes
GOODRAM may make changes to specifications and product descriptions at any time, without notice.
Product Sheet | GOODRAM PX400 SSD | V0.9 | © Wilk Elektronik SA – GOODRAM